



CALL 866-799-LIFT

WWW.LIFTSUPERSTORE.COM

LSS4P19FD/19FDXL

AUTOMOTIVE AND LIGHT TRUCK GENERAL SERVICE

100% DESIGNED AND BUILT IN NORTH AMERICA

PEGASUS

4 POST LIGHT DUTY COMMERICAL LIFT FOR SERVICING SMALL CARS OR LIGHT TRUCKS 19,000 LB. / 8.6T CAPACITY

DOUBLE WALL RUNWAYS WITH "Z" RAILS - 2 RUNWAYS

LENGTHS TO CHOOSE FROM



AVAILABLE IN GENERAL SERVICE OR FOR WHEEL ALIGNMENT

THE LIFTSUPERSTORE AND ALL IT'S REGISTERED TRADE MARKS ARE PART OF THE TLS LIFT
GROUP. PLEASE CALL US FOR PRODUCT INFORMATION ON COMMERCIAL AND HEAVY DUTY LIFT
PRODUCTS. WWW.TLSLIFTS.COM

October 2023



CONTACT US NOW WWW.LIFTSUPERSTORE.COM OR CALL 866-799-LIFT



4 POST SERVICE LIFT "PEGASUS" 19000 LB. / 8.6T CAPACITY



LSS4P19FD LSS4P19FDXL

	CATEGORY	CLOSED FRONT FOUR POST FLAT DECK SERVICE LIFT
	CAPACITY	19,000 LB. (8.6T)
A	RAISED HEIGHT	74" (1880MM)
В	LOWERED HEIGHT	10" (254MM)
С	OVERALL LENGTH EXTENDED	301 3/8" (7655MM)
С	OVERALL LENGTH STANDARD	274 3/8" (6969MM)
D	DECK LENGTH EXTENDED	238" (6045MM)
D	DECK LENGTH STANDARD	210 3/8" (5344MM)
E	WIDTH BETWEEN RUNWAYS	41" (1041MM)
F	RUNWAY DECK WIDTH	26" (660MM)
G	OVERALL WIDTH FRONT/REAR	150" (3810MM)
Н	MAX COLUMN HEIGHT	86" (2184MM)
	MAXIMUM WHEEL BASE EXT.	209" / 5309ММ
	MAXIMUM WHEEL BASE WB STD.	182" / 4623MM
	LIFT TIME	70 SECONDS
	ALI CERTIFIED WITH GOLD LABEL	YES
	POWER REQUIREMENTS	230V - 60HZ - 1PH - 25 AMP
	JACKING BEAM CAPACITY	9,000 LB. (4.1T)
	SHIPPING WEIGHT	5,000 LB. (2300 KG)

FEATURES

- BUILT TO HIGHER QUALITY STANDARD;
 100% NORTH AMERICAN MADE PREMIUM US BUCHER 2HP / 1.5KW
 POWER UNIT.
- CORROSION RESISTANT PROTECTION
 STEEL COMPONENTS ARE WHEEL A-BRATOR SHOT BLASTED AND ACID
 WASHED BEFORE A "DOUBLE BAKE"
 POWDER COAT FINISH IS APPLIED.
- PROVIDES LONGER LIFE NON FLEX
 DOUBLE WALL 23" / 584MM WIDE
 RUNWAYS WITH BUILT IN "Z" RAIL. HEAVY
 DUTY 10" X 8-3/8" X 1/4" WALL / 254MM X
 213MM X 6MM WALL COLUMNS AND 3" X
 8-1/4" / 72MM X 210MM TUBE TRAVERSE
 BEAMS.
- GREATER FLEXIBILITY WITH MORE
 MODELS TO CHOSE FROM AVAILABLE
 IN TWO RUNWAY LENGTHS WITH BUILT IN
 WHEEL ALIGNMENT OR SERVICE DECK.
 LIFT CAN BE ORDERED IN RED OR BLUE.
- PREMIUM OPTIONS AND ACCESSORIES
 CAN EXPAND THE CAPABILITIES AND
 SERVICE LIFE BUILT IN TIRE INFLATION
 HOSES, REMOVABLE WORK STEPS, LED
 RUNWAY LIGHTING AND PREMIUM LONG
 LIFE 5 YEAR WARRANTY HD JACKING
 BEAMS

- LOWER MAINTENANCE COSTS
 ZIRK STYLE GREASE FITTINGS AT ALL
 1-1/2" / 38MM PLATED HINGE PINS.
- EXTENDED LIFE "NON TWIST" CABLE
 DESIGN MACHINED STEEL NICKEL
 PLATED 9" / 229MM PULLEYS WITH
 BRONZE SELF LUBRICATING BUSHINGS.
 NON SPIN FATIGUE RESISTANT 9/16" /
 14MM CABLES ARE ROUTED ON DOUBLE
 STACKED PULLEYS (VERSUS FOUR
 STACKED) TO REDUCE STRESS AND WEAR.
- LOW PRESSURE HYDRAULICS PROVIDES LONGER LIFE - 4"ID X 65" / 102MM ID X 1651MM CYLINDER IS MOUNTED UNDER THE RUNWAY AND USE A PREMIUM "PARKER" SEAL AND WEAR RING WITH CHROME PLATED PLUNGER SHAFT.
- DESIGNED FOR OPTIMUM PRODUCTIVITY
 SINGLE POINT CONTROL
 WITH STAINLESS STEEL CYLINDER
 AIR RELEASES ENGAGE 12 LOCKING
 POSITIONS. ADJUSTABLE LOCKING
 LADDERS 81" X 2-3/4" X 3/8" / 2057MM
 X 70MM X 9.5MM THICK ALLOW FOR
 ACCURATE LEYELLING. THERE ARE
 COMPRESSED AIR OUTLETS FRONT
 AND REAR.

ADDITIONAL FEATURES



PREMIUM 9" (229MM) PULLEY AND CABLES 9/16" (14MM) CABLES

 \bigoplus




NORTH AMERICAN "BUCHER"


2 HP POWER UNIT



INCLUDES AIR REGULATOR
WATER TRAP OILER

EQUIPMENT FOOTPRINT





Disclaimer: TLS Inc. is constantly updating their products to maintain the highest possible standards of performance and safety. The specifications included in this brochure are only accurate at the time of printing and are subject to change without notice.

CONTACT US NOW

866-799-LIFT





AUTHORIZED TLS DISTRIBUTORS LOCATED: ALABAMA, ARIZONA, CALIFORNIA, FLORIDA,TEXAS, INDIANA, KANSAS, NEW ENGLAND, NEW HAMPSHIRE, WISCONSIN, MISSOURI, & VIRGINIA

DOUBLE WALL DECK WITH Z RAIL