



CALL 866-799-LIFT

WWW.LIFTSUPERSTORE.COM

LSSSL12FD/14FD/16FD

AUTOMOTIVE AND LIGHT TRUCK GENERAL SERVICE

100% DESIGNED AND BUILT IN NORTH AMERICA

SPACE LOGIC

PLATFORM SCISSOR LIGHT DUTY COMMERICAL LIFT FOR SER-VICING SMALL CARS OR LIGHT TRUCKS 12,000, 14,000 & 16,000 LB. (5.5, 6.4 & 7.3T)T CAPACITY

DOUBLE WALL RUNWAYS WITH "Z" RAILS - 2 RUNWAY
LENGTHS TO CHOOSE FROM





AVAILABLE IN GENERAL SERVICE OR OPTIONAL WHEEL ALIGNMENT

LSSSI 16FD

DECEMBER 2020

THE LIFTSUPERSTORE AND ALL IT'S REGISTERED TRADE MARKS ARE PART OF THE TLS LIFT GROUP. PLEASE CALL US FOR PRODUCT INFORMATION ON COMMERCIAL AND HEAVY DUTY LIFT PRODUCTS, WWW.TLSLIFTS.COM

OPTIONAL ACCESSORIES



▲ JACKING BEAM 6,000, 7,000 OR 8,000 LB. (2.7,3.2 OR 3.6T) CAPACITY



BUILT IN RUNWAY AIR INFLATION HOSES
& OPTIONAL FRONT RADIUS PLATES/
REAR SLIP PLATE



REMOVEABLE RUNWAY STEP PLAT-FORMS WITH NON SLIP SURFACE



ROLLING 30 GALLON WASTE OIL DRAIN

CONTACT US NOW WWW.LIFTSUPERSTORE.COM OR CALL 866-799-LIFT



LSSSL12FD LSSSL14FD LSSSL16FD

CATEGORY		SCISSOR SERVICE FLAT DECK		
	CAPACITY	12,000 LB.(5.4T)	14,000 LB.(6.35T)	16,000 LB. (7.3T)
	OPEN FRONT OR REAR	OPEN FRONT AND REAR		
	WHEEL ALIGNMENT	AVAILABLE WITH OPTIONAL WHEEL ALIGNMENT WITH BUILT IN RADIUS PLATE POCKETS & REAR SLIP PLATES		
A	RAISED HEIGHT	74" (1880MM)		
В	LOWERED HEIGHT	10 3/4" (273MM)		
С	OVERALL LENGTH	242 3/4" (6166M)	260 3/4" (6623MM)	
D	DECK LENGTH	185" (4700MM)	203" (5156мм)	
E	WIDTH BETWEEN RUNWAYS	41" (1041MM)		
F	RUNWAY DECK WIDTH	23" (584MM)		
G	OVERALL WIDTH	91 1/2" (2324MM)		
	ALI CERTIFIED WITH GOLD LABEL	YES		
	MAXIMUM WHEEL BASE	160" (4064MM)	178" ((4521MM)
	LIFT TIME	58 SECONDS		
	POWER REQUIREMENTS	230V - 60HZ - 1PH - 25 AMP		

Disclaimer: TLS Inc. is constantly updating their products to maintain the highest possible standards of performance and safety. The specifications included in this brochure are only accurate at the time of printing and are subject to change without notice.

FEATURES

- BUILT TO HIGHER QUALITY STANDARD; 100% NORTH AMERICAN MADE - PREMIUM US LEESON 3HP / 2.2KW MOTOR AND HPI PUMP.
- SUPERIOR STRUCTURAL STRENGTH PROVIDES LONGER LIFE - NON FLEX DOUBLE WALL RUNWAYS WITH BUILT IN "Z" RAIL AND HEAVY DUTY 3" X 6.5" X 3/8" / 76MM X 165MM X 9.5MM WALL TUBULAR LEGS
- GREATER FLEXIBILITY WITH MORE MODELS TO CHOSE FROM -AVAILABLE IN SURFACE OR FLUSH MOUNTED, ALIGNMENT OR SERVICE DECK AND A CHOICE OF FLOOR MOUNTED "CONSOLE" CONTROL OR SPACE SAVING WALL/FLOOR MOUNTED POWER UNIT WITH PENDANT CONTROL.
- PREMIUM OPTIONS AND
 ACCESSORIES CAN EXPAND THE
 CAPABILITIES AND SERVICE LIFE
 BUILT IN TIRE INFLATION HOSES,
 REMOVABLE WORK STEPS, LED
 RUNWAY LIGHTING AND PREMIUM
 HEAVY DUTY EXTENDED LIFE 5
 YEAR WARRANTY HD JACKING
 BEAMS
- LOWER MAINTENANCE COSTS
 -STEEL COMPONENTS ARE WHEEL A-BRATOR SHOT BLASTED AND

- ACID WASHED BEFORE A "DOUBLE BAKE" POWDER COAT FINISH IS APPLIED. ZIRK STYLE GREASE FITTINGS AT ALL HINGE POINTS. RUNWAY UNDER REAR SLIP PLATES IS OPEN TO PREVENT WATER AND DIRT COLLECTING.
- PCB CONTROL WITH LINEAR
 TRANSDUCERS CONTROL LEVEL
 TO WITHIN 5/32" / 4MM. THE FULL
 ADJUSTABLE FLOOR MOUNTED
 RACK AND PINION STYLE "GEAR
 BLOCKS" ALLOW FOR PRECISE
 LEVELLING.
- LOW PRESSURE HYDRAULICS PROVIDES LONGER LIFE - 2" X 6" / 51MM X 152MM "BREAK OUT" CYLINDERS ALLOW THE 25" X 4-1/2" / 635MM X 114MM ID CYLINDERS TO OPERATE AT <2500 PSI UNDER FULL LOAD.
- DESIGNED FOR GREATER
 TECHNICIAN PRODUCTIVITY THERE ARE NO OBSTRUCTIONS
 BETWEEN THE RUNWAYS OR
 BASE FRAME. THE LIFT RISES 74"
 / 1880MM IN 58 SECONDS WITH
 20 LOCKING POSITIONS. BUILT
 IN RUNWAY COMPRESSED AIR
 OUTLETS FRONT AND REAR.

ADDITIONAL FEATURES



 \bigoplus



DOUBLE WALL DECK WITH Z
RAIL




WALL/FLOOR MOUNT WITH PENDANT



SCISSOR RACK AND PINION STYLE GEAR RACK

EQUIPMENT FOOTPRINT





THE LIFTSUPERSTORE
RETAIL LOCATIONS THROUGHOUT THE USA &
CANADA

HEAD OFFICE & MANUFACTURING CENTRE 2300 SPEERS ROAD, OAKVILLE ONTARIO,

THE LIFTSUPERSTORE AND ALL IT'S REGISTERED TRADE MARKS ARE PART OF THE TLS LIFT GROUP. PLEASE CALL US FOR PRODUCT INFORMATION ON

COMMERCIAL AND HEAVY DUTY LIFT PRODUCTS.

