Itelift Lift it.Store it.Repair it SuperStore CALL 866-799-LIFT We make buying lifts easy! Space Logic

YOUR REPAIR EQUIPMENT HEADQUARTERS.

AUTOMOTIVE AND LIGHT TRUCK GENERAL SERVICE 100% DESIGNED AND BUILT IN NORTH AMERICA



CONTACT US NOW WWW.LIFTSUPERSTORE.COM OR CALL 866-799-LIFT (5438)

۲

SCISSOR FLAT DECK SERVICE LIFT -"SPACE LOGIC" 12,000, 14,000 OR 16,000 LB. / 6.8T CAPACITY



۲

LSSSL12FD LSSSL14FD LSSSL16FD

CATEGORY		SCISSOR SERVICE FLAT DECK			
	CAPACITY	12,000 lb.(5.4T)	14,000 lb.(6.35T)	16,000 lb. (7.3T)	
	OPEN FRONT OR REAR	Open Front and Rear			
	WHEEL ALIGNMENT	Available with optional wheel alignment with built in radius plate pockets & rear slip plates			
A	RAISED HEIGHT	74″ (1880mm)			
в	LOWERED HEIGHT	10 3/4" (273mm)			
С	OVERALL LENGTH	242 3/4" (6166m)	260 3/4" (6623mm)		
D	DECK LENGTH	185" (4700mm)	203" (5156mm)		
E	WIDTH BETWEEN RUNWAYS	41" (1041mm)			
F	RUNWAY DECK WIDTH	23" (584mm)			
G	OVERALL WIDTH	91 1/2" (2324mm)			
	ALI CERTIFIED WITH GOLD LABEL	YES			
	MAXIMUM WHEEL BASE	160" (4064mm)	178" (178" (4521mm)	
	LIFT TIME	58 seconds			
	POWER REQUIREMENTS	230V - 60Hz - 1Ph - 25 amp			
	RECOMMENDED JACKING BEAM CAPACITY	6,000 LB. (2.7T)	7,000 LB. (3.2T)	8,000 LB.(3.6T)	
Disclaimer: TLS Inc. is constantly updating their products to maintain the highest possible standards of performance and safety. The specifications included in					

ossible standards of performance and safety. The specifications included in this brochure are only accurate at the time of printing and are subject to change without notice

ADDITIONAL FEATURES

- Built to higher quality standard; 100% North American made premium US Leeson 3HP / 2.2kw motor and HPI pump.
- Superior structural strength provides longer life and more precise alignments - Non flex double wall runways with built in "Z" rail and heavy duty 3" x 6.5" x 3/8" / 76mm x 165mm x 9.5mm wall tubular leas
- Greater flexibility with more models to chose from - Available in surface or flush mounted, alignment or service deck and a choice of floor mounted "console" control or space saving wall/floor mounted power unit with pendant control.
- Premium options and accessories can expand the capabilities and service life - Stainless steel radius plates and rear steer plates, built in tire inflation hoses, removable work steps, LED runway lighting and premium heavy duty extended life 5 year warranty HD jacking beams
- · Lower maintenance costs -steel

components are wheel-a-brator shot blasted and acid washed before a "double bake" powder coat finish is applied. Zirk style grease fittings at all hinge points. Runway under rear slip plates is open to prevent water and dirt collecting.

- Precision levelling feature provides more accurate alignments - PCB Control with linear transducers control level to within 5/32"/4mm. The full adjustable floor mounted rack and pinion style "gear blocks" allow for precise levelling.
- · Low pressure hydraulics provides longer life - 2" x 6" / 51mm x 152mm "Break Out" cylinders allow the 25" x 4-1/2"

/ 635mm x 114mm ID cylinders to operate at <2500 psi under full load.

• Designed for greater technician productivity - there are no obstructions between the runways or base frame. The lift rises 74"/ 1880mm in 58 seconds with 20 locking positions. Built in runway

۲

EQUIPMENT FOOTPRINT







Enclosed Console Control

Double wall deck with Z rail



The Liftsuperstore Retail locations throughout the USA & Canada

Wall/Floor Mount with Pendent

Scissor Rack and Pinion style

Gear Rack

Head Office & Manufacturing Centre 2300 Speers Road, Oakville Ontario, L6L2X8 Call: 866-799-5438 Fax: 905-891-1214

()

May 2020

The Liftsuperstore and all it's registered trade marks are part of the TLS Lift Group. Please call us for product information on commercial and heavy duty lift products. www.tlslifts.com

۲