

# 1 POST STORAGE LIFT

6,000 LB. (2.7T) CAPACITY OPEN  
RUNWAYS OR FULL DECK



PARK MAGIC LSS1P6PL  
PARK MAGIC PLUS  
LSS1P6PLP

## TECHNICAL SPECIFICATIONS

| MODEL NUMBER                           | LSS1P6PL  | LSS1P6PLP                                       |
|--|---|---|
| FEATURE                                | OPEN RUNWAYS                                    | FULL DECK                                       |
| CAPACITY                               | 6,000 LBS / 2.7T                                | 6,000 LBS / 2.7T                                |
| OVERALL LENGTH WITH RAMPS              | 177" (4500MM)                                   | 157.5" ((4000MM)                                |
| RUNWAY LENGTH                          | 152" (3860MM)                                   | 141.7" (3600MM)                                 |
| DRIVE ON APPROACH ANGLE                | 13 DEGREES                                      | 14 DEGREES                                      |
| WIDTH OF BASE WITH OUTRIGGERS          | 59" (1500MM)                                    | 59" (1500MM)                                    |
| APPROACH RAMP LENGTH                   | 18.3" (465MM)                                   | 15.8" (401MM)                                   |
| WIDTH BETWEEN RUNWAYS                  | 37.4" OR 41.3" (950 OR 1050MM)                  | N/A   |
| RUNWAY/DECK WIDTH (INCLUDES RUB RAILS) | 19.7" (500MM)                                   | 84.6" (2150MM)                                  |
| WIDTH OUTSIDE RUNWAYS                  | 76.4" OR 80.7" (1941 OR 2050MM)                 | N/A   |
| OVERALL WIDTH (NO POWER UNIT)          | 105.7" (2685MM)                                 | 106.3" (2701MM)                                 |
| COLUMN HEIGHT                          | 118" (3000MM)                                   | 118" (3000MM)                                   |
| RUNWAY HEIGHT                          | 4-1/2" (114MM)                                  | 3 1/2" (119MM)                                  |
| LIFTING HEIGHT                         | 82.4" (2093MM)                                  | 82.4" (2093MM)                                  |
| MAX. CLEARANCE (UNDER RUNWAY)          | 78.7" (2000MM)                                  | 78.7" (2000MM)                                  |
| POWER SUPPLY                           | 110V 15 AMP 1HP .75KW 220V<br>8 AMP 2HP 1.5KW   | 110V 15 AMP 1HP .75KW 220V<br>8 AMP 2HP 1.5KW   |
| PUMP & MOTOR LOCATION                  | FRONT, BACK OR SIDE OF COLUMN                   | FRONT, BACK OR SIDE OF COLUMN                   |
| MECHANICAL LOCKING SYSTEM              | SINGLE POINT LOCK RELEASE WITH 17 LOCK POSITONS | SINGLE POINT LOCK RELEASE WITH 17 LOCK POSITONS |
| SHIPPING WEIGHT                        | 2250 LB. / 1023KG                               | 2650 LB. / 1205 KG                              |
| CONCRETE REQUIRED                      | 6" (152.4MM)                                    | 6" (152.4MM)                                    |

Disclaimer: The Liftsuperstore is constantly updating their products to maintain the highest possible standards of performance and safety. The specifications included in this brochure are only accurate at the time of printing and are subject to change without notice.

CONTACT US NOW

866-799-LIFT



THE LIFTSUPERSTORE  
HEADOFFICE & MANUFACTURING  
2300 SPEERS RD OAKVILLE ONTARIO



AUTHORIZED TLS DISTRIBUTORS LOCATED: ALABAMA,  
ARIZONA, CALIFORNIA, FLORIDA, TEXAS, INDIANA, KANSAS,  
NEW ENGLAND, NEW HAMPSHIRE, WISCONSIN, MISSOURI, &  
VIRGINIA