

2 POST STORAGE LIFT

6 & 7,000 LB. (2.7 & 3.2T)

CAPACITY



INTERLINK

LSS2P6PSRR1

LSS2P6PSWR1

LSS2P7PDXWR1

TECHNICAL SPECIFICATIONS

SPECIFICATION	LSS2P6PSRR1	LSS2P6PSWR1	LSS2P7PDXWR1
CAPACITY	6,000 LB. / 2.7T	6,000 LB. / 2.7T	7,000 LB. / 3.2T
NUMBER OF LIFTING CYLINDERS	1 CYLINDER	1 CYLINDER	2 CYLINDER
RUNWAY LENGTH WITH RAMPS	154 3/4" (3928 MM)	154 3/4" (3928 MM)	191.5" (4864 MM)
OVERALL WIDTH SINGLE LIFT	100 5/8" (2553MM)	108 1/4" (2743MM)	109" (2769MM)
INSIDE COLUMNS	87" (2210MM)	94 3/4" (2407MM)	95" (2413MM)
RUNWAY WIDTH	82 3/4" (2102MM)	90 1/2" (2299MM)	90.5" (2299MM)
LENGTH OF SIDE OUTRIGGER BARS	80 1/4" (2038MM)	80 1/4" (2038MM)	128" (3251MM)
COLUMN HEIGHT	118 1/2" (3010MM)	118 1/2" (3010MM)	138" (3505MM)
RUNWAY HEIGHT	4 1/4" (108MM)	4 1/4" (108MM)	4 1/4" (108MM)
LIFTING HEIGHT TO UNDER RUNWAY	84 1/4" (2140MM)	84 1/4" (2140MM)	84 1/4" (2140MM)
POWER TO LIFT CONTROLS	24V	24V	24V
LIFTING TIME	50 SECONDS	50 SECONDS	50 SECONDS
MOTOR	2 HP (1.5KW)	3 HP (2.2KW)	3 HP (2.2KW)
MECHANICAL LOCKING SYSTEM	17 FULL RANGE ANTI FALL LOCKS	17 FULL RANGE ANTI FALL LOCKS	17 FULL RANGE ANTI FALL LOCKS
POWER REQUIREMENT	220V / 60HZ / 1PH - 20 AMP	220V / 60HZ / 1PH - 20 AMP	220V / 60HZ / 1PH - 20 AMP
SHIPPING WEIGHT	2210 LB. / 1004 KG.	2520 LB. / 1004 KG	2820 LB. / 11159 KG.
SAFETY CONTROLS	PHOTOCELL SENSOR, EMERGENCY STOP BUTTON & LIMIT SWITCH	PHOTOCELL SENSOR, EMERGENCY STOP BUTTON & LIMIT SWITCH	PHOTOCELL SENSOR, EMERGENCY STOP BUTTON & LIMIT SWITCH

INSTALL 5 LIFTS IN ONLY 40' / 12.2 M (LSS2P6PSRR1)



USE OF A SHARED COLUMN

- * WITH TWO OR MORE LIFTS TOGETHER, EACH LIFT SHARES ONE COLUMN
- * USING LIFTS TOGETHER USING SHARED COLUMN(S) SAVES MONEY AND SPACE.

DISCLAIMER: TLS INC. IS CONSTANTLY UPDATING THEIR PRODUCTS TO MAINTAIN THE HIGHEST POSSIBLE STANDARDS OF PERFORMANCE AND SAFETY. THE SPECIFICATIONS INCLUDED IN THIS BROCHURE ARE ONLY ACCURATE AT THE TIME OF PRINTING AND ARE SUBJECT TO CHANGE WITHOUT NOTICE.

CONTACT US NOW

866-799-LIFT



THE LIFTSUPERSTORE
HEADOFFICE & MANUFACTURING
2300 SPEERS RD OAKVILLE ONTARIO



AUTHORIZED TLS DISTRIBUTORS LOCATED: ALABAMA, ARIZONA, CALIFORNIA, FLORIDA, TEXAS, INDIANA, KANSAS, NEW ENGLAND, NEW HAMPSHIRE, WISCONSIN, MISSOURI, & VIRGINIA